

**Description**

OETechAC is an organic solution of polysilanes

**Areas of Application**

OETechAC is used as a cleaning agent and adhesion promoter of OETech Urethanes.

**Technical Data**

| Color                   | Viscosity                  | Density At 68 °F | Conventional Solids Content (EN 827) | Application Temperature | Specific Data                      |
|-------------------------|----------------------------|------------------|--------------------------------------|-------------------------|------------------------------------|
| Transparent, colourless | Extremely low (ca 1 mPa.s) | Ca 0.80          | 97 %                                 | 59 to 86 °F Drying time | Drying time at 68°F : 30 to 60 sec |

**Instructions for Use**

Substrates preparation :

The substrates to be assembled must be dry and dust free. When using solvents, extinguish all sources of ignition and carefully follow the safety and handling instructions given by the manufacturer or supplier.

Application :

Thoroughly shake the product before use. OETechAC may be applied with a lint-free wool dauber. Close immediately the bottle after use. If OETechAC gets cloudy, do not use it anymore. OETech AC is a clear solvent/activator which cleans all contaminates from the glass surface and prepares it for urethane bonding. It must be wiped from the surface while still in the liquid state.

**Storage and Shelf Life**

12 months in the original, hermetically sealed and unopened packaging between 32 and 86 °F.  
1 month after first opening in the original, hermetically sealed packaging between 32 and 86 °F.

**Packaging**

6 – 4 oz aluminum bottles per case.

**Safety**

Highly flammable. See material safety data sheet before use.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired.

Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.

Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.

See also material safety data sheet.

---